

# RS Calibration hoses

## Lite

PVC-coated fabric hose with overlapping welded seam  
Heatable up to a maximum of 40 °C  
Can bent up to 90°  
Available from DN 80 to DN 200

## LiteTube

PVC-coated fabric hose with sewn and welded seam  
Heatable up to a maximum of 80 °C  
Can be bent up to 90°  
Available from DN 100 to DN 300

## LitePlus

PVC-coated fabric hose with welded seam  
Heatable up to a maximum of 80° C  
Can be bent up to 90°  
Available from DN 100 to DN 300

## LiteBlue

PVC-coated fabric hose with sewn and welded seam  
Heatable up to a maximum of 80 °C  
Extra flexible with lightweight fabric  
Available from DN 100 to DN 300

## HotPlus

PVC coated fabric hose with welded surface seam  
Heatable up to a maximum of 80 °C  
Not bendable  
Available from DN 200 to DN 400, further dimensions upon request

*Calibration hoses  
LiteBlue*



*Calibration hoses  
HotPlus*



## Preliner

PE film tube with welded seam

Serves as an outer film to protect the liner from ground water and seepage water

*Preliner*



## PU-Outer hose

Thin polyester felt layer with PU coating

Serves as preliner and DIBt-approved integrated external coating

Prevents excess resin in the inlets

*PU-Outer hose*

